



CHEMISTRY BETWEEN US

PL 44-190 Knurów, ul. Przemysłowa 22, phone: +48 32 335 79 00, e-mail: firma@aibsc.com.pl

Integra Vario

Integra Vario – tape based on a special smart membrane with a variable value of S_d , which makes it a versatile solution for both internal and external applications. This eliminates the possibility of errors during application of the film. These films are made in two versions:

- **Integra Vario Silver** – with an adhesive strip for mounting to the window frame;
- **Integra Vario Gold** – with an adhesive strip for mounting to the window frame and a butyl ribbon to adhere to the wall.



● Integra Vario Silver



● Integra Vario Gold Single Sided



● Integra Vario Gold Double Sided



Specifications – universal tape Integra Vario

Property	Standard	Results	
Water tightness	EN 1027	Class 9A	own testing
Vapour permeability	EN 12572	Sd from 1,05 to 12 m	
Flammability class	EN 13501-1	B	
Adhesion of the adhesive	EN 1939	0,5 N/mm	
Tensile strength	EN 12311-3	≥ 6 Mpa	
Tear strength	EN 12311-3	≥ 60%	
Air permeability	EN 1026	class 4	
Odporność na UV		3 months	
Shelf life		1 year	Storage in a dry place at a temperature of +1 to +25°C

Available widths	70 mm	100 mm	150 mm
Package – quantity per box	4 rolls	3 rolls	2 rolls
Quantity per pallet	480 rolls	360 rolls	240 rolls
Application temperature from +5 to +35°C	Individually packaged rolls are also available		